


order number: L00000E0065

Patch Cord Cat.5e MP8 100-0,5 m, red



Technical Attributes	
Short name	MP8 100-0,5
Length	0,5 m
Colour	red

Performance Characteristics

- pin assignment acc. to EIA/TIA 568B
- 90° / 180° / 270° moulded boot with latch protection
- Colours: grey, green, red, blue, yellow, black, white, purple
- Variants with very short boot
- 360 degrees completely surround plug shielding (shielded cable types)
- flexible and strain relieved
- moulded strain relief boot
- cable jacket and strain relief boot: PVC resp. LSZH (= Low Smoke, Zero Halogen)

Mechanical Characteristics	
Cable structure	Li2YY 4x2xAWG 24/7
Stranded wire	AWG 24 (7/0.2 mm)
Insulation	PE; Ø 0.96 (±0.05 mm)
Pair shielding	
Overall shielding	
Outer jacket	5.4 mm (±0.2 mm)

Climatic Characteristics	
flame-retardant test	IEC 60332-1
UL	
Operating temperature in °C	-20° C to 60° C

Electrical Characteristics	
Current carrying capacity at 50°C	1 A
PoE+ acc to IEEE 802.3at	Adequate for Power over Ethernet+

Standards	
Connectors	IEC 60603-7-2

Transmission Characteristics	
10 Gigabit Ethernet	
Gigabit Ethernet acc. to IEEE 802.3	Adequate for Gigabit Ethernet